

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015
Version: 1.0

Page: 1/10
(2015-USA/ENG-BFLV1.0)

1. Identification

Product identifier used on the label

STYROPEK BFL Series

Recommended use of the chemical and restriction on use

Recommended use*: for industrial processing only; Expanding-agent containing plastic for the production of foam plastics

* The "Recommended use" identified for this product is provided solely to comply with a US Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
Styropek México SA de CV
Fernando Montes de Oca 71
Col. Condesa, C.P. 06140,
MEXICO DF

Telephone: +52 55 9140 0523

Emergency telephone number

Tel.: 832-446-6154 (in USA)
CHEMTREC Int.: +1-703-527-3887

Other means of identification

Synonyms: Polystyrene

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR Part 1910.1200

Classification of the product

No need for classification according to GHS criteria for this product.

Label elements

Hazard Statement:

EUH018 In use may form flammable/explosive vapour-air mixture.

Precautionary Statement:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015
Version: 1.0

Page: 2/10
(2015-USA/ENG-BFLV1.0)

P233 Keep container tightly closed.
P243 Take precautionary measures against static discharge.
P403 + P235 Store in a well-ventilated place. Keep cool.

Hazards not otherwise classified

May cause some eye irritation which should cease after removal of the product.

Labeling of special preparations (GHS):
Product releases a flammable hydrocarbon.

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Emergency overview

WARNING:
FLAMMABLE.
Releases flammable vapour.
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. CONTAINS MATERIAL WHICH MAY CAUSE KIDNEY DAMAGE BASED ON ANIMAL DATA.
Eye wash fountains and safety showers must be easily accessible.
Use with local exhaust ventilation.
Avoid contact with the skin, eyes and clothing.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Content (W/W)	Chemical name
78-78-4	>= 0.3 - < 3.0 %	isopentane
109-66-0	>= 3.0 - < 7.0 %	Pentane
25637-99-4	>= 0.2 - < 1.0 %	hexabromocyclododecane
78169-20-7	>= 0.0 - < 0.1 %	Sulfonium compounds, C11-14 -alkylbis(hydroxyethyl), 2-hydroxyethyl sulfates (salts)

According to Regulation 1994 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Content (W/W)	Chemical name
9003-53-6	>= 92.0 %	polystyrene
109-66-0	<= 6.0 %	Pentane
78-78-4	<= 1.5 %	isopentane

4. First-Aid Measures

Description of first aid measures

General advice:
Remove contaminated clothing.

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015
Version: 1.0

Page: 3/10
(2015-USA/ENG-BFLV1.0)

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If difficulties occur: Seek medical attention.

If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

If swallowed:

No hazards anticipated. Rinse mouth and then drink plenty of water. If difficulties occur: Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: headache, dizziness, incoordination, dazed state, Eye irritation, skin irritation

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to the symptoms under clinical conditions.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
dry powder, water spray, carbon dioxide, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
Substance/product is dangerous when exposed to heat or flames.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

When large quantities of solid substance/product are involved, melting may occur, in which condition, application of water may cause extensive scattering of molten material. Dense smoke produced during combustion may obscure vision. To prevent re-ignition of interior, target center of fire with large amounts of water. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015
Version: 1.0

Page: 4/10
(2015-USA/ENG-BFLV1.0)

6. Accidental release measures

Further accidental release measures:
High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Sources of ignition should be kept well clear. Extinguish sources of ignition nearby and downwind. Avoid dust formation. Avoid inhalation. Ensure adequate ventilation. Wear appropriate respiratory protection.

Environmental precautions

Discharge into the environment must be avoided. Do not release untreated into natural waters.

Methods and material for containment and cleaning up

Sweep/shovel up. Avoid raising dust. Ensure adequate ventilation. Place into suitable containers for reuse or disposal in a licensed facility. After decontamination, spill area can be washed with water.

7. Handling and Storage

Precautions for safe handling

Upon delivery, trailer and/or container should be opened and allowed to vent for a minimum of one (1) hour before unloading. The substance/product in bead or expanded form generates static charges during handling which are difficult to dissipate due to the insulating properties. Take precautionary measures against static discharges. Containers should be opened carefully in wellventilated areas to avoid static discharge. Maintain air circulation and ventilation at a minimum rate of six air changes per hour to prevent the formation of flammable concentrations.

Protection against fire and explosion:

Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy. Substance/product is capable of accumulating a static charge which could act as an ignition source. Wear non-sparking safety shoes. Ground conductive equipment properly to prevent electrostatic discharge. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Higher line velocity can increase the build-up of static electric charge.

Conditions for safe storage, including any incompatibilities

Segregate from strong oxidizing agents.

Storage stability:

Maintain relative humidity at 40% to minimize static accumulation.
Avoid prolonged storage at high temperatures.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Pentane	Exposure	TWA value 600 ppm 1,800 mg/m ³ ; STEL
---------	----------	--

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015
Version: 1.0

Page: 5/10
(2015-USA/ENG-BFLV1.0)

limits	value 760 ppm 2,250 mg/m ³ ;
NIOSH	REL value 120 ppm 350 mg/m ³ ; Ceil_Time
Pocket Guide to Chemical Hazards (US)	610 ppm 1,800 mg/m ³ ;

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Respiratory protection may not be required under normal operating conditions if adequate ventilation is provided. Wear respiratory protection if ventilation is inadequate. Breathing protection if dusts are formed.

Hand protection:

non-static gloves (e.g. of leather)

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Anti-static protective clothing, Antistatic safety shoes

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts/mists/vapours. Eye wash fountains and safety showers must be easily accessible. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	beads	
Odour:	of pentane	
Colour:	white	
pH value:		not soluble
softening point:	approx. 71 °C	
onset of boiling:		The substance / product decomposes therefore not determined.
Sublimation point:		No applicable information available.
Flash point:	79 - 85 °C	(ASTM D3278)
Flammability:	not highly flammable	(UN Test N.1 (ready combustible solids))
Flammability of Aerosol Products:		not applicable, the product does not form flammable aerosoles)
Lower explosion limit:	1.4 %(V)	(air)
Upper explosion limit:	8.3 %(V)	(air)
Autoignition:	285 °C	(DIN 51794)
Vapour pressure:		not applicable
Density:	approx. 1.02 –	(20 °C)

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015
Version: 1.0

Page: 6/10
(2015-USA/ENG-BFLV1.0)

Bulk density:	1.05 g/cm ³ approx. 640 kg/m ³	(20 °C)
Vapour density:		Heavier than air.
Partitioning coefficient noctanol/ water (log Pow):		not applicable
Self-ignition temperature:		not self-igniting
Thermal decomposition:		No applicable information available.
Viscosity, kinematic:		No applicable information available.
Solubility in water:		not soluble
Miscibility with water:		immiscible
Solubility (quantitative):		No applicable information available.
Solubility (qualitative):	soluble	
Evaporation rate:	solvent(s): aromatic hydrocarbons, organic solvents, ketones,	The product is a non-volatile solid.

10. Stability and Reactivity

Reactivity

No applicable information available.

Corrosion to metals:

No corrosive effect on metal.

Oxidizing properties:

Not an oxidizer.

Chemical stability

No applicable information available.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid electro-static discharge.

Incompatible materials

strong oxidizing agents, aromatic solvents

Hazardous decomposition products

Decomposition products:

Possible thermal decomposition products: gases/vapours, monomers, cyclic low molecular weight oligomers, oxides, hydrocarbons

Thermal decomposition:

No applicable information available.

11. Toxicological information

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015
Version: 1.0

Page: 7/10
(2015-USA/ENG-BFLV1.0)

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Contact with molten product may cause thermal burns.

Information on: isopentane

Assessment of acute toxicity: Aspiration may result in chemical pneumonitis, which may be fatal.

Oral

Type of value: LD50

Value: > 2,000 mg/kg

Inhalation

Type of value: LC50

Value: > 5 mg/l

Dermal

Type of value: LD50

Value: > 2,000 mg/kg

Irritation / corrosion

Assessment of irritating effects: Frequent and prolonged contact can lead to skin irritation.

Information on: Sulfonium compounds, C11-14-alkylbis(hydroxyethyl), 2-hydroxyethyl sulfates (salts)

Assessment of irritating effects: Corrosive! Damages skin and eyes.

Skin

Prolonged contact with the product can result in skin irritation.

Eye

Similar findings as for skin apply to eyes.

Sensitization

Assessment of sensitization: There is no evidence of a skin-sensitizing potential.

Result: Non-sensitizing.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The substance is inert.

Information on: isopentane

Assessment of repeated dose toxicity: Chronic overexposure has been shown to cause adverse kidney effects in experimental animals.

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015
Version: 1.0

Page: 8/10
(2015-USA/ENG-BFLV1.0)

Genetic toxicity

Assessment of mutagenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Carcinogenicity

Assessment of carcinogenicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Reproductive toxicity

Assessment of reproduction toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Other Information

Information on: Pentane
Has a degreasing effect on skin.

Symptoms of Exposure

Headache, dizziness, incoordination, dazed state, Eye irritation, skin irritation

12. Ecological Information

Toxicity

Aquatic toxicity

Information on: Pentane
Assessment of aquatic toxicity:
Acutely toxic for aquatic organisms.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

On the basis of the data available concerning eliminability/degradation and bioaccumulation potential, longer-term harm to the environment is improbable.

Elimination information

Non-biodegradable.

Bioaccumulative potential

Bioaccumulation potential

The product will not be readily bioavailable due to its consistency and insolubility in water.

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015
Version: 1.0

Page: 9/10
(2015-USA/ENG-BFLV1.0)

Additional information

Add. remarks environm. fate & pathway:

Because of the product's consistency and low water solubility, bioavailability is improbable.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Do not discharge into waterways or sewer systems without proper authorization.

Container disposal:

Dispose of in accordance with national, state and local regulations. Uncontaminated packaging can be recycled. Contact manufacturer regarding recycling.

14. Transport Information

Land transport

TDG

Hazard class: 9
Packing group: III
ID number: UN 2211
Hazard label: 9
Proper shipping name: POLYMERIC BEADS, EXPANDABLE

Sea transport

IMDG

Hazard class: 9
Packing group: III
ID number: UN 2211
Hazard label: 9
Marine pollutant: NO
Proper shipping name: POLYMERIC BEADS, EXPANDABLE

Air transport

IATA/ICAO

Hazard class: 9
Packing group: III
ID number: UN 2211
Hazard label: 9
Proper shipping name: POLYMERIC BEADS, EXPANDABLE

15. Regulatory Information

Federal Regulations

Not applicable

Safety Data Sheet

STYROPEK® BFL Series

Revision date : 03/01/2015

10/10

Version: 1.0

Page:

(2015-USA/ENG-BFLV1.0)

NFPA Hazard codes:

Health : 1

Fire: 2

Reactivity: 1

Special:

HMIS III rating

Health: 1

Flammability: 2

Physical hazard:0

16. Other Information

SDS Prepared by:

Styropek Product Regulations

SDS Prepared on: 03/01/2015

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

STYROPEK is a registered trademark of SYTOROPEK DE MEXICO SA DE CV or STYROPEK USA, INC. IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF DATA SHEET